

Section 3.1 – Development Services

APPENDIX 5

POLICY 3.1.7
RETAINING WALLS - SUBDIVISION

OBJECTIVE:

To control the height and bulk of subdivision retaining walls to ensure that the amenity of the urban environment is not compromised by inappropriate development.

DEFINITIONS

“boundary fence” means a boundary fence referred to in section 16 of the Dividing Fences Act 1961.

“height” means the vertical distance from the natural ground level to the top of the wall.

“lot” shall have the same meaning provided within the Residential Design Codes of Western Australia.

“Natural ground level” shall have the meaning provided within the Residential Design Codes.

“non sacrificial graffiti protection” means a coating applied to a fence or wall, which is not removed in the process of removing graffiti.

“public place” means any place to which the public has access.

“Retaining Wall” means a wall designed to retain soil and superimposed load.

“Subdivision Retaining Wall” shall mean a wall designed to retain soil resulting from earthworks associated with compliance with a condition of subdivisional approval issued by the Western Australian Commission and pursuant to Section 20D of the Town Planning and Development Act 1928.

POLICY AREA

This policy applies to the whole of the City of Joondalup.

POLICY STATEMENTS

Excessive retaining is discouraged. The raised height of buildings and the overlooking of an adjoining property resulting in the potential loss of privacy is a matter the City will have particular regard to when assessing retaining wall proposals.

Section 3.1 – Development Services

- 1 A building licence must be obtained from the City prior to any work commencing on the construction of a proposed retaining wall.
- 2 Where an owner(s) of a lot fills that lot above the natural ground level then that owner(s) has an obligation to support that fill through the construction of a retaining wall wholly within the boundaries of the owner(s) lot.
- 3 Where an owner(s) of a lot excavates soil then that owner(s) must provide support for any adjoining lot and superimposed loads, through the construction of a retaining wall wholly within the boundaries of the owner(s) lot.
- 4 The Manager Infrastructure Management and Ranger Services may approve subdivision retaining walls not exceeding three (3) metres in height. However, where the subdivisional retaining wall abuts a lot in different ownership then the relevant provisions of the Residential Design Codes shall apply.
- 5 The Principal Building Surveyor is authorised to issue a building licence for any retaining wall which has been approved under point 4 above.
- 6 Subdivision retaining walls in excess of 3 metres in height require Council approval.
- 7 Subdivision retaining walls are to be designed in accordance with the City's guidelines for development and subdivision of land.
- 8 Alternatives to slab on ground construction are to be encouraged where it is obvious that due to the gradient and characteristics of the site, major excavation or filling as a result of raft slab construction would be inappropriate.
- 9 Retaining walls abutting a public place shall be treated with a non-sacrificial anti-graffiti coating.
- 10 Where any vegetation on adjoining land has been disturbed for the purposes of subdivision works it shall be rehabilitated within twenty-eight (28) days upon completion of the project. In the interim, erosion control measures must comply with Council Policy 5.3.2 *Sand Drift Control* and Private Property Local Law 1998.

Section 3.1 – Development Services

POLICY 3.1.7
RETAINING WALLS - SUBDIVISION**OBJECTIVE:**

To control the height and bulk of subdivision retaining walls to ensure that the amenity of the urban environment is not compromised by inappropriate development.

DEFINITIONS

“boundary fence” means a boundary fence referred to in section 16 of the Dividing Fences Act 1961.

“height” means the vertical distance from the natural ground level to the top of the wall.

“lot” shall have the same meaning provided within the Residential Design Codes of Western Australia.

“Natural ground level” shall have the meaning provided within the Residential Design Codes.

“non sacrificial graffiti protection” means a coating applied to a fence or wall, which is not removed in the process of removing graffiti.

“public place” means any place to which the public has access.

“Retaining Wall” means a wall designed to retain soil and superimposed load.

“Subdivision Retaining Wall” shall mean a wall designed to retain soil resulting from earthworks associated with compliance with a condition of subdivisional approval issued by the Western Australian Commission and pursuant to Section 20D of the Town Planning and Development Act 1928.

POLICY AREA

This policy applies to the whole of the City of Joondalup.

POLICY STATEMENTS

Excessive retaining is discouraged. The raised height of buildings and the overlooking of an adjoining property resulting in the potential loss of privacy is a matter the City will have particular regard to when assessing retaining wall proposals.

- 1 A building licence must be obtained from the City prior to any work commencing on the construction of a proposed retaining wall.

Section 3.1 – Development Services

- 2 Where an owner(s) of a lot fills that lot above the natural ground level then that owner(s) has an obligation to support that fill through the construction of a retaining wall wholly within the boundaries of the owner(s) lot.
- 3 Where an owner(s) of a lot excavates soil then that owner(s) must provide support for any adjoining lot and superimposed loads, through the construction of a retaining wall wholly within the boundaries of the owner(s) lot.

~~4~~ The Principal Building Surveyor is authorised to issue a building licence for any retaining wall which:

- ~~_____ (a) does not exceed 1.2 metres in height or a total of 3 metres when combined with a boundary fence;~~
- ~~_____ (b) complies where necessary with an approval to commence development;~~
- ~~_____ (c) is an approved subdivisional retaining wall; or~~
- ~~_____ (d) exceeds 1.2 metres in height up to 2 metres upon receipt of favourable comments from adjoining owners.~~

- 4 The Manager Infrastructure Management and Ranger Services may approve subdivision retaining walls not exceeding three (3) metres in height. However, where the subdivisional retaining wall abuts a lot in different ownership then the relevant provisions of the Residential Design Codes shall apply.

~~5 The Manager Infrastructure Management and Ranger Services may approve subdivision retaining walls not exceeding three (3) metres in height. However, where the subdivisional retaining wall abuts a lot in different ownership then the relevant provisions of the Residential Design Codes shall apply.~~

5 The Principal Building Surveyor is authorised to issue a building licence for any retaining wall which has been approved under point 4 above.

- 66 Subdivision retaining walls in excess of 3 metres in height require Council approval.
- 77 Subdivision retaining walls are to be designed in accordance with the City's guidelines for development and subdivision of land.
- 88 Alternatives to slab on ground construction are to be encouraged where it is obvious that due to the gradient and characteristics of the site, major excavation or filling as a result of raft slab construction would be inappropriate.
- 99 Retaining walls abutting a public place shall be treated with a non-sacrificial anti-graffiti coating.

Section 3.1 – Development Services

~~10~~10 Where any vegetation on adjoining land has been disturbed for the purposes of subdivision works it shall be rehabilitated within twenty-eight (28) days upon completion of the project. In the interim, erosion control measures must comply with Council Policy 5.3.2 *Sand Drift Control* and Private Property Local Law 1998.